


REV	DESCRIPTION	DATE	BY	ECN
–	INITIAL RELEASE	–	–	10401
1	AFTER PROTO REV. MOVED SPLICE G AND SPLICE H	05/19/14	BWD	10725

ALL CONNECTORS SHOWN ARE LOAD VIEW UNLESS OTHERWISE NOTED.
ALL WIRE MUST BE 125°C UNLESS OTHERWISE NOTED.
LOOM AS NOTED BY ——
LOOM SHOULD HAVE RATING OF 125°C MINIMUM.
TOLERANCES:
± 1" ≤ 36"
± 2" > 36"
REFERENCE TEE0939.XLS FOR CUTLIST

SPECIAL NOTES:

THOR MOTOR COACH


DRAWN BY: BWD | SHEET: 1 OF 1 | DATE: 03/14/14

DESCRIPTION: CHASSIS HARNESS

MODEL: 37TB

© CONFIDENTIAL AND PROPRIETARY INFORMATION OF THOR MOTOR COACH. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT OUR EXPRESSED WRITTEN CONSENT IS PROHIBITED.

DRAWING NUMBER: TEE0939 | REVISION: 1



REV	DESCRIPTION	DATE	BY	ECN
–	–	–	–	10097
1	ADDED 3RD SLIDE WIRES	12/27/13	BWD	10253
2	ADD AWNING SWITCH GROUND WIRE	9/10/14	NWG	11070
3	ADD AWNING WIRES FOR AWNING 3 AND REMOVED THE 20A FUSE LOCATION	11/14/14	SR	

ALL CONNECTORS SHOWN ARE LOAD VIEW UNLESS OTHERWISE NOTED.
ALL WIRE MUST BE 125°C UNLESS OTHERWISE NOTED.
LOOM AS NOTED BY ——
LOOM SHOULD HAVE RATING OF 125°C MINIMUM.
TOLERANCES:
± 1° ≤ 35°
± 2° > 35°

SPECIAL NOTES:

THOR MOTOR COACH

DRAWN BY: MCH | SHEET: 1 OF 1 | DATE: 5/10/13

DESCRIPTION: LCI 8 FUNCTION REMOTE

MODEL: 37MD, 37KT, 37LS

© CONFIDENTIAL AND PROPRIETARY INFORMATION OF THOR MOTOR COACH. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT OUR EXPRESSED WRITTEN CONSENT IS PROHIBITED.

DRAWING NUMBER: TEE0655 | REVISION: 3